DATA SHEET

PRINTED ON
23-04-2026

EARTHMAX SR 53

TIRE SIZE	**23.5 R 25**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	BULDOZER / ÎNCĂRCĂTOR / AUTOBASCULANTĂ CU PROFIL REDUS (LPDT)
VERSION	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	201 A2

DIMENSIUNI US STANDARD

USA CODE	94062362	**RIM REC**	19.50/2.5
OD (IN)	65.6	**TRA CODE**	L5
SLR (IN)	29.8	**STAR RATING**	★★
RC (IN)	197.4		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	76	80	83	87	91	94
5	27600	28300	29100	30000	30900	32000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..