

# PL 801

<b>TIRE SIZE</b>	7.00 - 15
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	ANCINHO ROTATIVO / CEIFEIRA / EMPILHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / EMPILHADOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TT



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94007233	<b>RIM ALT</b>	4.33 R; 5.0
<b>SW (IN)</b>	7.9	<b>PR</b>	12
<b>OD (IN)</b>	29.5		
<b>RIM REC</b>	5.5		

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>120</b>
<b>15 LOAD WHEEL</b>	6770
<b>15 STEER WHEEL</b>	5205
<b>5 OTHER VEHICLES</b>	6770
<b>15 OTHER VEHICLES</b>	5205
<b>STATIC SIDE LOADER</b>	7860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.