


RIDEMAX FL 690

TIRE SIZE	800/60 R 32
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKER / TRAILER / IMPLEMENTS / TRAILER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	185 D



DIMENSIONS IS STANDARD

SW (MM)	800	RIM REC	DH 27 B
OD (MM)	1800	RIM ALT	DW 27 B
SLR (MM)	817	ECE	E11-106R-006480
RC (MM)	5454	SRI	850

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2695	3455	4295	4885	5645	6400	6990	7665	8420
65	2960	3795	4720	5365	6200	7030	7680	8420	9250
50	3585	4590	5710	6495	7505	8510	9295	10190	11195
40	4030	5160	6420	7300	8430	9565	10445	11450	12580
30	4475	5730	7125	8105	9360	10620	11600	12715	13970
25	4680	5995	7455	8480	9795	11110	12135	13300	14615
10	5330	6830	8495	9660	11160	12655	13820	15155	16650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.