


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>540/65 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	150 D ; 153 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94029150	<b>RC (IN)</b>	173.3
<b>SW (IN)</b>	20.9	<b>RIM REC</b>	W 16 L
<b>OD (IN)</b>	57.6	<b>RIM ALT</b>	W 18 L
<b>SLR (IN)</b>	26.4	<b>ECE</b>	E4-106R-000651

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	3550	4140	4660	5170	5690	6140	6800	7400
30	3730	4350	4890	5430	5990	6450	7140	7760
25	3870	4510	5070	5630	6210	6680	7410	8050
20	4090	4760	5360	5950	6550	7050	7830	8500
5 LT	4760	5540	6240	6930	7630	8220	9120	9900
5 HT	4090	4760	5360	5950	6550	7050	7830	8500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.