

# BK 823

<b>TIRE SIZE</b>	<b>9.00 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТРАКТОР- ТЯГАЧ / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS</b>	127 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94040131	<b>RC (IN)</b>	101.7
<b>SW (IN)</b>	9.6	<b>RIM REC</b>	6.5
<b>OD (IN)</b>	35.1	<b>ECE</b>	E11-106R-003604
<b>SLR (IN)</b>	15.5	<b>PR</b>	14

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>64</b>
25	3860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.