


AGRIMAX RT 600

TIRE SIZE	650/75 R 32
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN / SPRIDARE / TRAKTOR / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	172 A8/B



DIMENSIONER US STANDARD

USA CODE	94055968	RC (IN)	213.2
SW (IN)	25.8	RIM REC	DW 21 B
OD (IN)	70.4	RIM ALT	DW 20 B ; DW 23 B
SLR (IN)	31.8	ECE	E11-106R-004755

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46	49	55
30	6390	7360	9030	9870	10840	11810	12790	13890	-	-
25	6390	7360	9030	9870	10840	11810	12790	13890	-	-
20	6840	7880	9670	10560	11610	12640	13690	14870	-	-
5 LT	8560	9880	12100	13230	14530	15830	17130	18620	-	-
5 HT	6840	7880	9670	10560	11610	12640	13690	14870	-	-
5 CYC.	-	10520	13460	14760	17120	18770	20550	22320	22670	23610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.