


AGRIMAX RT 765M

| | |
|---------------------|--|
| TYRE SIZE | 710/70 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | SPECIAL |
| TYRE TYPE | TL |
| LI/SS | 166 D |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 716 | RIM REC | DW 23 B |
| OD (MM) | 1959 | RIM ALT | DW 25 B |
| SLR (MM) | 859 | ECE | E11-106R-005837 |
| RC (MM) | 5751 | SRI | 925 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 2915 | 3395 | 3870 | 4350 | 4825 | 5300 |
| 50 | 3065 | 3565 | 4065 | 4565 | 5065 | 5565 |
| 40 | 3195 | 3720 | 4240 | 4765 | 5285 | 5805 |
| 30 | 3355 | 3905 | 4450 | 5000 | 5550 | 6095 |
| 10 LT | 3910 | 4550 | 5190 | 5830 | 6470 | 7105 |
| 10 HT | 3355 | 3905 | 4450 | 5000 | 5550 | 6095 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.