

AGRIMAX RT 765

TIRE SIZE	380/70 R 24
UM	IS STANDARD
MACHINERY	PULVERIZADOR / TRACTOR / VENDIMIADORA / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	SPECIAL
TIRE TYPE	TL
LI/SS	125 D



DIMENSIONES IS STANDARD

SW (MM)	380	ECE	E11-106R-005767
OD (MM)	1190	SRI	575
SLR (MM)	538	TRA CODE	R1W
RC (MM)	3560	TREAD DEPTH (MM)	41,5
RIM REC	W 12	TKPH (TK/H)	1
RIM ALT	W 11 ; W 13		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	910	1060	1205	1355	1505	1650
50	955	1115	1270	1425	1580	1735
40	1000	1160	1325	1485	1650	1810
30	1045	1220	1390	1560	1730	1900
10 LT	1220	1420	1620	1820	2020	2215
10 HT	1045	1220	1390	1560	1730	1900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.