

# TR 135

|                     |                   |
|---------------------|-------------------|
| <b>TIRE SIZE</b>    | <b>18.4 - 30</b>  |
| <b>UM</b>           | IS STANDARD       |
| <b>CONSTRUCTION</b> | ⊠ BIAS            |
| <b>MACHINERY</b>    | TRACTOR / TRAILER |
| <b>VERSION</b>      | HD                |
| <b>TIRE TYPE</b>    | TT                |
| <b>LI/SS</b>        | 149 A6            |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 460  | <b>RIM REC</b> | W 16 L          |
| <b>OD (MM)</b>  | 1545 | <b>RIM ALT</b> | W 15 L          |
| <b>SLR (MM)</b> | 697  | <b>ECE</b>     | E11-106R-004436 |
| <b>RC (MM)</b>  | 4712 | <b>PR</b>      | 12              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.30</b> |
| 30                | 3250        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.