


# AGRIMAX SPARGO

<b>TIRE SIZE</b>	<b>VF 380/90 R 54</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	176 D



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94075614	<b>RC (IN)</b>	245.4
<b>SW (IN)</b>	15.1	<b>RIM REC</b>	W13
<b>OD (IN)</b>	80.9	<b>RIM ALT</b>	DW 13; DW 12; W 12
<b>SLR (IN)</b>	37.3	<b>ECE</b>	E11-106R-0010081

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64
45	6230	6960	7830	8550	8990	9420	9700	9990	10500	11010	11450	11880	12240	12600	12970	13320	13900	14480
<b>FROM 40 TO 25</b>	6740	7520	8460	9240	9720	10180	10500	10810	11360	11910	12370	12850	13230	13630	14010	14410	15040	15660
20	6880	7680	8640	9430	9910	10390	10710	11030	11590	12150	12630	13110	13510	13900	14300	14710	15350	15980
12	7020	7820	8800	9620	10100	10600	10920	11250	11810	12380	12870	13360	13770	14170	14580	14980	15630	16290
5	7410	8270	9310	10170	10690	11200	11550	11890	12490	13100	13610	14120	14550	14980	15410	15860	16540	17220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.