

# AW 705

<b>TIRE SIZE</b>	16.0/70 - 20
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	151 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94027408	<b>RC (IN)</b>	131.6
<b>SW (IN)</b>	16.3	<b>RIM REC</b>	13.0
<b>OD (IN)</b>	42.7	<b>RIM ALT</b>	12 SDC; 13 SDC; 14
<b>SLR (IN)</b>	19.0	<b>ECE</b>	E4-106R-002711

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44
5 FR	10650
15 FR	9050
20 FR	8520
25 FR	7610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.