DATA SHEET

PRINTED ON
23-04-2026

AGRIMAX RT 955

	340/85 R 46
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	ILAÇLAMA / ÜZÜM HASAT MAKINESI / BIÇERDÖVER / UYGULAMALI MAKINE
VERSION	STANDARD
TIRE TYPE	TL
	150 A8/B

UNDEFINED IS STANDARD

SW (MM)	353	**RIM REC**	W 12
OD (MM)	1746	**RIM ALT**	W 11
SLR (MM)	826	**ECE**	E4-106R-001828
RC (MM)	5346	**SRI**	850

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
50	1445	1880	2280	2480	2650	2915	3150	3350	-
40	1445	1880	2280	2480	2650	2915	3150	3350	-
30	1545	2010	2440	2655	2835	3120	3370	3585	-
10	2065	2665	3220	3520	3770	4125	4475	4775	5025

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..