

# TF 8181

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 7.50 - 20                              |
| <b>UM</b>           | US STANDARD                            |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                 |
| <b>MACHINERY</b>    | TRATTORE 2WD / TRATTORE /<br>RIMORCHIO |
| <b>VERSIONE</b>     | STANDARD                               |
| <b>TIRE TYPE</b>    | TT                                     |
| <b>LI/SS</b>        | 99 A8                                  |



## DIMENSIONI US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CODICE USA</b> | 94020683 | <b>RC (IN)</b> | 107.3          |
| <b>SW (IN)</b>    | 8.1      | <b>RIM REC</b> | 5.50 F         |
| <b>OD (IN)</b>    | 36.0     | <b>RIM ALT</b> | 5.00 F         |
| <b>SLR (IN)</b>   | 17.0     | <b>ECE</b>     | E4-106R-002635 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>44</b> |
| 25               | 1710      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.