

# TR 171

|                     |             |
|---------------------|-------------|
| <b>TIRE SIZE</b>    | 11.2 - 24   |
| <b>UM</b>           | IS STANDARD |
| <b>CONSTRUCTION</b> | ❖ BIAS      |
| <b>MACHINERY</b>    | TRACTEUR    |
| <b>VERSION</b>      | STANDARD    |
| <b>TIRE TYPE</b>    | TT          |
| <b>LI/SS</b>        | 120 A6      |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 285  | <b>RIM REC</b> | W 10            |
| <b>OD (MM)</b>  | 1105 | <b>RIM ALT</b> | W 9             |
| <b>SLR (MM)</b> | 517  | <b>ECE</b>     | E11-106R-004478 |
| <b>RC (MM)</b>  | 3403 | <b>PR</b>      | 10              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.00</b> |
| 30                | 1400        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.