

# MULTIMAX MP 513

<b>TIRE SIZE</b>	425/55 R 17 MPT
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ / ТЕХНИКА ДЛЯ ВНЕСЕНИЯ УДОБРЕНИЙ / УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	134 G



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94038411	<b>RC (IN)</b>	106.1
<b>SW (IN)</b>	16.6	<b>RIM REC</b>	13
<b>OD (IN)</b>	35.4	<b>RIM ALT</b>	13.00
<b>SLR (IN)</b>	15.7	<b>ECE</b>	E4-54R-0024098

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	36	44	51
55	2380	2820	3420	4030	4670
40	2590	3060	3710	4390	5080
25	2740	3250	3940	4640	5380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.