


# AS 504

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>6.5/80 - 12</b>  |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       |  BIAS            |
| <b>MACHINERY</b>          | SOLLEVATORE TELESOPICO /<br>RIMORCHIO DA CAMPO / ATTREZZI<br>AGRICOLI / SOLLEVATORE<br>TELESOPICO |
| <b>VERSIONE</b>           | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 80 A8   |
| <b>LI/SS FREE ROLLING</b> | 93 A8   |



## DIMENSIONI US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CODICE USA</b> | 94038602 | <b>RC (IN)</b> | 72.3           |
| <b>SW (IN)</b>    | 6.7      | <b>RIM REC</b> | 5 J            |
| <b>OD (IN)</b>    | 23.9     | <b>RIM ALT</b> | 5 JA           |
| <b>SLR (IN)</b>   | 11.1     | <b>ECE</b>     | E4-106R-002180 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 52   |
|-----------|------|
| 5 FR      | 2010 |
| 15 FR     | 1710 |
| 20 FR     | 1610 |
| 25 FR     | 1430 |
| 5 DW      | 1390 |
| 15 DW     | 1180 |
| 20 DW     | 1110 |
| 25 DW     | 990  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.