

EARTHMAX SR 51 SP



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 51 SP

EARTHMAX SR 51 SP is an All-Steel radial tyre specifically developed for medium-sized wheel loaders operating in severe mining and quarrying environments. The reinforced, strong casing delivers maximum performance during demanding loading, dozing, and load-and-carry operations on mixed surfaces, such as unpaved roads, gravel, and crushed rock. Thanks to its high rubber volume and tread density, the deep L5 tread combines high traction with excellent resistance to damage while the non-directional design ensures uniform driving characteristics and extended wear resistance. Moreover, the cut-resistant compound provides extraordinary protection against punctures. All these features ensure minimized downtime and a long service life, making EARTHMAX SR 51 SP a highly efficient tyre under heavy-duty conditions.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	26.5 R 25	TL	L5	**	209 A2	22.00/3.0	-	0	705	1772	806	5334	86	CR
	29.5 R 25	TL	L-5	**	216 A2	25.00/3.5	-	0	775	1901	862	5722	93	CR
Ø33"	35/65 R33	TL	L5	**	224 A2	28.00/3.5	-	0	905	2061	872	6082	95	CR
	35/65 R33	TL	L5	***	229 A2	28.00/3.5	-	0	905	2061	872	6082	95	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES		
					
					

Permissible tolerances: O.D. 2%–5.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026



TECHNOLOGIES		PERFORMANCES				
	 L-5/L5					
	 A2					
						
						
						

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026