

## DESERT KING

|                     |                     |
|---------------------|---------------------|
| <b>TIRE SIZE</b>    | <b>29.5 - 25 DT</b> |
| <b>UM</b>           | US STANDARD         |
| <b>CONSTRUCTION</b> | BIAS                |
| <b>MACHINERY</b>    | DESERT TRUCK        |
| <b>VERSION</b>      | STANDARD            |
| <b>TL/TT</b>        | TL                  |



### DIMENSIONS US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>USA CODE</b> | 94069057 | <b>RC (IN)</b>  | 212.3     |
| <b>SW (IN)</b>  | 30.3     | <b>RIM REC</b>  | 25.00/3.5 |
| <b>OD (IN)</b>  | 71.7     | <b>PR</b>       | 28        |
| <b>SLR (IN)</b> | 30.9     | <b>TRA CODE</b> | E7        |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 36    |
|-----------|-------|
| 5         | 29100 |
| 30        | 22000 |
| 40        | 18200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.