


RIDEMAX FL 693 M



TIRE SIZE	710/50 R 26.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CISTERNA MÓVEL / REBOQUE / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	170 D

DIMENSÕES US STANDARD

CÓDIGO USA	94037315	RC (IN)	166.0
SW (IN)	28.6	RIM REC	AG 24.00
OD (IN)	54.4	RIM ALT	AG 20.00
SLR (IN)	24.6	ECE	E4-106R-001422

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58
45	4450	5050	6130	7100	8180	9260	9980	11060	12010
40	4890	5560	6750	7800	8990	10180	10980	12170	13230
30	5930	6720	8170	9450	10890	12330	13290	14730	16000
25	6670	7560	9180	10610	12230	13860	14940	16560	17990
15	7740	8780	10660	12330	14220	16090	17350	19230	20900
5	8820	10010	12150	14050	16190	18340	19760	21910	23810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.