


AGRIMAX RT 657

TIRE SIZE	540/65 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	152 D ; 155 A8



DIMENSIONER IS STANDARD

SW (MM)	530	RIM REC	W 16 L
OD (MM)	1566	RIM ALT	W 18 L
SLR (MM)	712	ECE	E4-106R-000652
RC (MM)	4742	SRI	750

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1705	1990	2240	2485	2735	2950	3270	3550
50	1795	2090	2350	2615	2875	3100	3435	3730
40	1860	2170	2445	2715	2985	3220	3565	3875
30	1965	2290	2575	2860	3150	3395	3760	4085
10 LT	2285	2670	3000	3335	3670	3955	4380	4760
10 HT	1965	2290	2575	2860	3150	3395	3760	4085

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.