


AGRIMAX V- FLECTO

TIRE SIZE	VF 710/60 R 30
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	171 D



DIMENSÕES US STANDARD

CÓDIGO USA	94513505	RC (IN)	189.0
SW (IN)	28.3	RIM REC	DW 25 B
OD (IN)	64.0	RIM ALT	DW 24 B; DW 27 B
SLR (IN)	27.6	ECE	E11-106R-0010832

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	6040	7020	8130	9130	10110	11100	12330
FROM 40 TO 25	6640	7730	8940	10030	11110	12200	13560
20	6770	7870	9120	10220	11330	12430	13820
12	6900	8040	9300	10430	11550	12690	14100
5	7300	8500	9830	11030	12220	13410	14910
*UPTO 5 CYC WITH FRONT LOADER	9290	10810	12520	14040	15560	17070	18980
5 HT	6770	7870	9120	10220	11330	12430	13820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.