


# EARTHMAX SR 23

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>15.5 R 25</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MOTONIVELADORA / PALA<br>CARGADORA   |
| <b>VERSIÓN</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 146 A8 ; 169 A2  |



## DIMENSIONES IS STANDARD

|                 |           |                    |       |
|-----------------|-----------|--------------------|-------|
| <b>OD (MM)</b>  | 1264      | <b>TRA CODE</b>    | G2/L2 |
| <b>SLR (MM)</b> | 559       | <b>STAR RATING</b> | ★     |
| <b>RC (MM)</b>  | 3756      |                    |       |
| <b>RIM REC</b>  | 12.00/1.3 |                    |       |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.25 | 1.50 | 1.75 | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 40         | 1550 | 1750 | 2000 | 2180 | 2360 | 2575 | 2800 | 3000 | -    | -    | -    | -    | -    |
| 10         | -    | -    | -    | -    | -    | -    | -    | -    | 5000 | 5150 | 5450 | 5600 | 5800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.