


RT 747 AGRO INDUSTRIAL

TIRE SIZE	500/70 R 24
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PALA COMPATTA / SOLLEVATORE TELESCOPICO / PALA COMPATTA / SOLLEVATORE TELESCOPICO
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	157 A8 ; 154 B



DIMENSIONI IS STANDARD

SW (MM)	485	RIM REC	DW 16 L
OD (MM)	1320	RIM ALT	DW 15 L ; DW 18 L
SLR (MM)	585	ECE	E11-106R-002988
RC (MM)	3949	SRI	625

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.0
50	1765	2175	2550	2965	3340	3750
40	1940	2395	2805	3260	3670	4125
30	2075	2560	3000	3490	3930	4415
25	2155	2655	3115	3620	4075	4580
10 CYC	2910	3590	4210	4890	5510	6190
STATIC	4075	5025	5890	6845	7710	8665

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.