

# MULTIMAX MP 527

**460/70 R 24 IND****UM** US STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** KÜÇÜK YÜKLEYİCİ / TELESKOPIK  
YÜKLEYİCİ / KÜÇÜK YÜKLEYİCİ /  
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TL

159 A8/B

**UNDEFINED US STANDARD**

<b>USA CODE</b>	94052097	<b>RC (IN)</b>	149.6
<b>SW (IN)</b>	18.3	<b>RIM REC</b>	DW 15 L
<b>OD (IN)</b>	49.4	<b>RIM ALT</b>	DW 14 L ; DW 16 L
<b>SLR (IN)</b>	22.6	<b>ECE</b>	E11-106R-002983

**LOAD CAPACITY (LBS/TIRE)**

MPH / PSI	23	29	35	41	46	51	58	61	64
30	4630	5500	6270	7140	8010	8590	9640	-	-
25	4630	5500	6270	7140	8010	8590	9640	-	-
20	4960	5900	6720	7650	8580	9190	10330	-	-
15	5150	6120	6970	7940	8900	9550	10710	-	-
5 CYC.	5650	6960	8180	9410	10710	11650	13170	13900	14470
STATIC	8660	10660	12540	14430	16420	17870	20190	21310	22190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.