

AGRIMAXFACTOR

620/70 R 38

UM IS STANDARD

CONSTRUCTION  RADIAL

MACHINERY TRAKTÖR

VERSION STANDARD

TIRE TYPE TL

170 D ; 173 A8



UNDEFINED IS STANDARD

SW (MM)	625	RIM REC	DW 20 B
OD (MM)	1833	RIM ALT	DW 18 L; W 18 L
SLR (MM)	844	ECE	E11-106R-0010338
RC (MM)	5580	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
65	2535	2990	3445	3835	4290	4680	5135	5525	5580	6000
50	2665	3140	3620	4030	4505	4915	5395	5805	5860	6300
40	2780	3280	3775	4205	4700	5130	5625	6055	6115	6570
30	2920	3440	3965	4415	4935	5385	5910	6355	6420	6900
10 LT	3400	4010	4620	5140	5750	6275	6885	7405	7480	8040
10HT	2920	3440	3965	4415	4935	5385	5910	6355	6420	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.