


AGRIMAX V- FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 710/60 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR DE ALTA POTENCIA / TRACTOR |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 171 D |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94058563 | RC (IN) | 214.4 |
| SW (IN) | 27.9 | RIM REC | DW 25 B |
| OD (IN) | 71.7 | RIM ALT | DW 23 B |
| SLR (IN) | 31.3 | ECE | E11-106R-004520 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|--------------------------------------|-------|-------|-------|-------|-------|-------|
| 45 | 6780 | 7890 | 8990 | 10110 | 11220 | 12330 |
| FROM 40 TO 25 | 7450 | 8670 | 9890 | 11110 | 12330 | 13560 |
| 20 | 7590 | 8840 | 10070 | 11330 | 12580 | 13820 |
| 12 | 7750 | 9020 | 10270 | 11550 | 12820 | 14100 |
| 5 | 8190 | 9530 | 10870 | 12210 | 13560 | 14910 |
| *UPTO 5 CYC WITH FRONT LOADER | 10430 | 12140 | 13830 | 15550 | 17260 | 18980 |
| 5 HT | 7590 | 8840 | 10070 | 11330 | 12580 | 13820 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.