


FL 695

| | |
|---------------------|--|
| TIRE SIZE | 710/50 R 30.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | REMORCĂ / MAȘINI DE IMPLEMENTARE / REMORCĂ |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 177 D |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 700 | RIM REC | AG24.00 |
| OD (MM) | 1490 | RIM ALT | AG20.00 |
| SLR (MM) | 691 | ECE | E11-106R-008661 |
| RC (MM) | 4553 | SRI | 700 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.5 | 5.0 |
|------------|------|------|------|------|------|------|------|-------|-------|-------|-------|
| 65 | -- | -- | -- | 3725 | 4310 | 4895 | 5405 | 5915 | 6500 | 6935 | 7300 |
| 50 | -- | -- | -- | 4510 | 5215 | 5920 | 6540 | 7160 | 7865 | 8395 | 8835 |
| 40 | -- | 3675 | 4470 | 5065 | 5860 | 6655 | 7350 | 8045 | 8840 | 9435 | 9930 |
| 30 | 3200 | 4080 | 4965 | 5625 | 6505 | 7390 | 8160 | 8935 | 9815 | 10475 | 11025 |
| 25 | 3350 | 4270 | 5195 | 5885 | 6810 | 7730 | 8540 | 9345 | 10270 | 10960 | 11535 |
| 20 | 3495 | 4460 | 5425 | 6145 | 7110 | 8075 | 8915 | 9760 | 10725 | 11445 | 12045 |
| 10 | 3815 | 4865 | 5915 | 6705 | 7755 | 8805 | 9725 | 10645 | 11695 | 12485 | 13140 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.