

FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 550/45 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 147 A8/144 B |
| LI/SS FREE ROLLING | 159 A8/156 B |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 525 | RIM REC | AG 16.00 |
| OD (MM) | 1070 | ECE | E4-106R-002309 |
| SLR (MM) | 488 | PR | 16 |
| RC (MM) | 3253 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.40 | 2.60 | 2.80 |
|------------|------|------|------|
| 10 FR | 5600 | 5865 | 6125 |
| 20 FR | 5040 | 5280 | 5515 |
| 30 FR | 4480 | 4695 | 4900 |
| 40 FR | 4000 | 4190 | 4375 |
| 50 FR | 3600 | 3770 | 4000 |
| 10 DW | 3935 | 4125 | 4305 |
| 20 DW | 3540 | 3710 | 3875 |
| 30 DW | 3145 | 3300 | 3445 |
| 40 DW | 2810 | 2945 | 3075 |
| 50 DW | 2530 | 2650 | 2800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.