

FLOTATION 648

TIRE SIZE	600/55 - 22.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	156 A8/153 B
LI/SS FREE ROLLING	169 A8/166 B



DIMENSIONES IS STANDARD

SW (MM)	600	RIM REC	AG 20.00
OD (MM)	1230	ECE	E4-106R-001564
SLR (MM)	540	PR	16
RC (MM)	3716		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.20	2.40	2.60
10 FR	7365	7750	8120
20 FR	6630	6975	7310
30 FR	5890	6200	6495
40 FR	5260	5535	5800
50 FR	4735	4980	5300
10 DW	5080	5340	5600
20 DW	4575	4805	5040
30 DW	4065	4275	4480
40 DW	3630	3815	4000
50 DW	3265	3435	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.