

# AGRIMAX RT 855

|           |                                                                                 |
|-----------|---------------------------------------------------------------------------------|
| TIRE SIZE | 480/80 R 42                                                                     |
| UM        | US STANDARD                                                                     |
| MACHINERY | PULVERIZADOR / VENDIMIADORA /<br>TRACTOR / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| VERSIÓN   | STANDARD                                                                        |
| TIRE TYPE | TL                                                                              |
| LI/SS     | 151 A8/B                                                                        |

## DIMENSIONES US STANDARD

|            |          |         |                            |
|------------|----------|---------|----------------------------|
| CÓDIGO USA | 94021796 | RC (IN) | 216.3                      |
| SW (IN)    | 18.9     | RIM REC | W 16 A ; DD 16 ; DW 16 A   |
| OD (IN)    | 72.2     | RIM ALT | DD 16 L ; DW 16 L ; W 16 L |
| SLR (IN)   | 32.9     | ECE     | E4-106R-000791             |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23    |
|-----------|------|------|------|------|------|-------|
| 30        | 4190 | 4870 | 5560 | 6240 | 6920 | 7600  |
| 25        | 4190 | 4870 | 5560 | 6240 | 6920 | 7600  |
| 20        | 4490 | 5210 | 5950 | 6680 | 7420 | 8150  |
| 5 LT      | 5610 | 6530 | 7450 | 8370 | 9280 | 10200 |
| 5 HT      | 4490 | 5210 | 5950 | 6680 | 7420 | 8150  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

