


# FL 639

**850/40 R 26.5**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	YAYICI / UYGULAMALI MAKINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	173 D ; 184 A8



## UNDEFINED US STANDARD

<b>USA CODE</b>	94064779	<b>RC (IN)</b>	162.3
<b>SW (IN)</b>	33.9	<b>RIM REC</b>	AG 28.00
<b>OD (IN)</b>	53.3	<b>ECE</b>	E11-106R-006228
<b>SLR (IN)</b>	23.6		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58
45	4180	5360	6660	7570	8740	9920	10820	11870	13040
40	4590	5870	7310	8310	9600	10890	11890	13040	14330
30	5560	7110	8850	10060	11620	13180	14400	15780	17340
25	6350	8130	10120	11510	13290	15080	16470	18050	19840
20	6930	8870	11040	12550	14510	16450	17970	19700	21640
15	7250	9290	11550	13140	15180	17220	18790	20610	22640
5	8260	10580	13160	14970	17280	19610	21420	23480	25790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.