


AGRIMAX V- FLECTO

TIRE SIZE	VF 600/65 R 34 NRO
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	169 D



DIMENSÕES US STANDARD

CÓDIGO USA	94070275	RC (IN)	195.0
SW (IN)	23.5	RIM REC	DW 21 B
OD (IN)	64.7	RIM ALT	DW 20 B
SLR (IN)	28.8	ECE	E11-106R-007603

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5360	6170	7100	7910	8840	9660	10820	11630
FROM 40 TO 25	5890	6780	7800	8700	9720	10610	11890	12790
20	6010	6910	7960	8870	9920	10820	12140	13040
12	6120	7050	8110	9050	10110	11030	12370	13290
5	6470	7460	8590	9570	10690	11680	13080	14060
*UPTO 5 CYC WITH FRONT LOADER	8240	9490	10920	12180	13610	14860	16650	17900
5 HT	6010	6910	7960	8870	9920	10820	12140	13040

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.