


# TR 315

<b>TIRE SIZE</b>	<b>23X10.50 - 12</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / МАШИНА ДЛЯ СБОРА ФРУКТОВ / ТРАНШЕЙНЫЙ ЭКСКАВАТОР / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	255	<b>RIM REC</b>	8½ JA
<b>OD (MM)</b>	600	<b>RIM ALT</b>	7 JA
<b>SLR (MM)</b>	272	<b>ECE</b>	E11-106R-005206
<b>RC (MM)</b>	1840	<b>PR</b>	10

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.80</b>
15	1100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.