

EARTHMAX SR 30 M



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 30 M

EARTHMAX SR 30 M is an All-Steel radial tyre specifically engineered for medium-sized wheel loaders operating primarily at industrial sites and factories on smooth, paved surfaces but also travelling occasionally on public roads. Thanks to its versatility, ensured by the tread pattern and compound, the tyre provides reliable performance on both hard surfaces and uneven terrain, making it suitable for mixed applications in industrial, construction, and civil environments. EARTHMAX SR 30 M features an optimized tread design that minimizes vibrations and noise, ensuring superior driving comfort and a smooth ride, especially over longer distances. In addition, the reduced rolling resistance provides enhanced fuel efficiency and contributes to lower operating costs during transport and load & carry operations.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	23.5 R 25	TL	E3/L3	**/*	185 B 195 A2	19.5/2.5	-	210	605	1605	711	4797	34	CR
	23.5 R 25	TL	L3	**	201 A2	19.50/2.5	-	-	605	1605	711	4797	34	CR

CR: CUT RESISTANT COMPOUND



TECHNOLOGIES		PERFORMANCES					
							
E3/L3	B						
201 kg							

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026