


# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 800/70 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE RECOLTARE / TRACTOR DE MARE PUTERE / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	192 D



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	794	<b>RIM REC</b>	DW 27 B
<b>OD (MM)</b>	2150	<b>RIM ALT</b>	DW 25 B; DW 28 B; DW 30 B
<b>SLR (MM)</b>	950	<b>ECE</b>	E11-106R-006481
<b>RC (MM)</b>	6400	<b>SRI</b>	1025

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
70	3980	4690	5405	6020	6730	7345	8055	8670	9485	10195
<b>FROM 65 TO 40</b>	4370	5155	5940	6610	7395	8065	8850	9520	10420	11200
30	4545	5360	6175	6875	7690	8390	9205	9905	10835	11650
20	4720	5570	6415	7140	7990	8715	9560	10285	11255	12100
10	5550	6545	7540	8395	9390	10245	11240	12095	13230	14225
<b>UPTO 30 CYC</b>	5680	6700	7720	8595	9610	10485	11505	12380	13545	14560
<b>UPTO 15 CYC</b>	6775	7990	9205	10245	11460	12500	13715	14760	16145	17360
<b>UPTO 10 CYC</b>	7430	8760	10095	11235	12570	13710	15045	16185	17710	19040
10HT	4545	5360	6175	6875	7690	8390	9205	9905	10835	11650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.