

# TR 135

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>16.9 - 34</b>   |
| <b>UM</b>        | IS STANDARD        |
| <b>MACHINERY</b> | TRAKTOR / SLÄPVAGN |
| <b>VERSION</b>   | HD                 |
| <b>TIRE TYPE</b> | TT                 |
| <b>LI/SS</b>     | 142 A6             |



## DIMENSIONER IS STANDARD

|                 |        |                         |                 |
|-----------------|--------|-------------------------|-----------------|
| <b>SW (MM)</b>  | 429    | <b>ECE</b>              | E11-106R-004440 |
| <b>OD (MM)</b>  | 1585   | <b>PR</b>               | 10              |
| <b>SLR (MM)</b> | 728    | <b>SRI</b>              | 750             |
| <b>RC (MM)</b>  | 4794   | <b>TRA CODE</b>         | R1              |
| <b>RIM REC</b>  | W 15 L | <b>TREAD DEPTH (MM)</b> | 37,5            |
| <b>RIM ALT</b>  | W 14 L | <b>TKPH (TK/H)</b>      | 0               |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>2.00</b> |
|-------------------|-------------|
| 30                | 2650        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.