


# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 800/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE RECOLTARE / TRACTOR DE MARE PUTERE / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	184 D



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94055784	<b>RC (IN)</b>	243.5
<b>SW (IN)</b>	31.3	<b>RIM REC</b>	DW 27 B
<b>OD (IN)</b>	82.1	<b>RIM ALT</b>	DW 25 B; DW 28 B; DW 30 B
<b>SLR (IN)</b>	36.3	<b>ECE</b>	E11-106R-006497

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	8480	9920	11360	12630	13900	14980	16790	18050
<b>FROM 40 TO 25</b>	9330	10910	12500	13890	15820	16470	18450	19800
20	9690	11340	13000	14440	15880	17120	19180	20630
12	10060	11780	13490	14990	16490	17780	19920	21430
5	11840	13860	15870	17640	19400	20910	23420	25200
<b>UPTO 20 CYC</b>	12110	14190	16250	18050	19850	21410	23980	25790
<b>UPTO 10 CYC</b>	14450	16910	19370	21530	23680	25520	28590	30750
<b>UPTO 5 CYC</b>	15850	18550	21240	23610	25970	27990	31360	33730
5 HT	9690	11340	13000	14440	15880	17120	19180	20630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.