

## RT 857

|                  |                    |
|------------------|--------------------|
| <b>TYRE SIZE</b> | <b>460/85 R 30</b> |
| <b>UM</b>        | IS STANDARD        |
| <b>MACHINERY</b> | TRACTOR            |
| <b>VERSION</b>   | STANDARD           |
| <b>TL/TT</b>     | TL                 |
| <b>LI/SS</b>     | 145 A8/B           |

### DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 475  | <b>RIM REC</b> | W 16 L          |
| <b>OD (MM)</b>  | 1544 | <b>RIM ALT</b> | W 15 L ; W 14 L |
| <b>SLR (MM)</b> | 697  | <b>ECE</b>     | E4-106R-001480  |
| <b>RC (MM)</b>  | 4648 | <b>SRI</b>     | 725             |

### LOAD CAPACITY (KG/TYRE)

| KM/H / BAR  | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|-------------|------|------|------|------|------|------|
| <b>50</b>   | 1595 | 1860 | 2120 | 2380 | 2640 | 2900 |
| <b>40</b>   | 1595 | 1860 | 2120 | 2380 | 2640 | 2900 |
| <b>30</b>   | 1710 | 1990 | 2270 | 2550 | 2830 | 3105 |
| <b>10LT</b> | 2140 | 2490 | 2840 | 3190 | 3540 | 3890 |
| <b>10HT</b> | 1710 | 1990 | 2270 | 2550 | 2830 | 3105 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

