


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>480/80 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	164 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	DW 16 A; W 16 A; DD 16
<b>OD (MM)</b>	1936	<b>RIM ALT</b>	W 16 L; DD 16 L; DW 16 L
<b>SLR (MM)</b>	895	<b>ECE</b>	E4-106R-000798
<b>RC (MM)</b>	5871	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	2295	2635	2975	3315	3655	3955	4250	4650	5000
40	2295	2635	2975	3315	3655	3955	4250	4650	5000
30	2460	2825	3185	3550	3915	4235	4550	4975	5350
10 LT	3080	3535	3990	4445	4900	5300	5695	6230	6700
10 HT	2460	2825	3185	3550	3915	4235	4550	4975	5350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.