


# RIB 774 (A)

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>18X8.50 - 8</b>  |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       |  BIAS        |
| <b>MACHINERY</b>          | PRESSA PER BALLE DI FIENO /<br>MIETITREBBIA / RIMORCHIO /<br>MIETITREBBIA / ATTREZZI AGRICOLI |
| <b>VERSIONE</b>           | ARAMID BELTED   |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS FREE ROLLING</b> | 85 A8   |



## DIMENSIONI US STANDARD

|                   |          |                |                               |
|-------------------|----------|----------------|-------------------------------|
| <b>CODICE USA</b> | 94064809 | <b>RC (IN)</b> | 54.7                          |
| <b>SW (IN)</b>    | 8.9      | <b>RIM REC</b> | 7.00   - 55 ;   - 70 ;   - 90 |
| <b>OD (IN)</b>    | 18.1     | <b>ECE</b>     | E11-106R-006268               |
| <b>SLR (IN)</b>   | 8.5      | <b>PR</b>      | 6                             |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 44   |
|-----------|------|
| 5 FR      | 1590 |
| 15 FR     | 1360 |
| 20 FR     | 1270 |
| 25 FR     | 1140 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.