


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 650/60 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE A ELEVATA POTENZA / TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 D



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94001222	<b>RC (IN)</b>	196.7
<b>SW (IN)</b>	26.0	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	66.0	<b>RIM ALT</b>	DW21B
<b>SLR (IN)</b>	29.5	<b>ECE</b>	E11-106R-007210

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	5740	6640	7540	8550	9340	10120	11240
<b>FROM 40 TO 25</b>	6300	7290	8280	9390	10250	11110	12350
20	6430	7440	8440	9580	10460	11340	12600
12	6560	7580	8610	9770	10660	11560	12840
5	6930	8010	9100	10330	11280	12220	13580
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	8820	10210	11580	13140	14350	15560	17280
5 HT	6430	7440	8440	9580	10460	11340	12600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.