

PUDDLE SPECIAL (B)

TIRE SIZE	120/90 - 26
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	SPRAYER / IMPLEMENTS
VERSION	STANDARD
TIRE TYPE	TT
LI/SS	94 A2



DIMENSIONS US STANDARD

USA CODE	94514601	RC (IN)	112.1
SW (IN)	5.0	RIM REC	4 JA
OD (IN)	37.0	ECE	E11-106R-0011399
SLR (IN)	17.6	PR	8

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	52
5	1480
MPH / PSI	14
45	5450
FROM 40 TO 25	5980
20	6100
12	6220
5*	6570
MPH / PSI	9
30	1510
25	1510
20	1620
5	2260
MPH / PSI	9
40	3820
30	4020
25	4190
15	4400
5 LT	5130
5 HT	4400
MPH / PSI	9
40	1810
30	1910
25	1970
15	2080

MPH / PSI	52
5 LT	2420
5 HT	2080
MPH / PSI	9
45	5610
FROM 40 TO 25	9250
20	9440
12	9620
5	10170
*UPTO 20 CYC	10500
*UPTO 10 CYC	12530
*UPTO 5 CYC	13730
10HT	9440
MPH / PSI	9
45	5610
FROM 40 TO 25	6160
20	6290
12	6420
5	6780
*UPTO 20 CYC	7000
*UPTO 10 CYC	8360
*UPTO 5 CYC	9160
10HT	6290

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..