

# TR 273

|                     |                  |
|---------------------|------------------|
| <b>TIRE SIZE</b>    | <b>23.1 - 26</b> |
| <b>UM</b>           | IS STANDARD      |
| <b>CONSTRUCTION</b> | ⊠ BIAS           |
| <b>MACHINERY</b>    | TRATOR           |
| <b>VERSÃO</b>       | STANDARD         |
| <b>TIRE TYPE</b>    | TT               |
| <b>LI/SS</b>        | 156 A6           |



## DIMENSÕES IS STANDARD

|                 |      |                 |                  |
|-----------------|------|-----------------|------------------|
| <b>SW (MM)</b>  | 590  | <b>RIM REC</b>  | DW 20 A; DW 20 B |
| <b>OD (MM)</b>  | 1655 | <b>ECE</b>      | E11-106R-004628  |
| <b>SLR (MM)</b> | 737  | <b>PR</b>       | 14               |
| <b>RC (MM)</b>  | 5053 | <b>TRA CODE</b> | R2               |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.00</b> |
| 30                | 4000        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.