

MINE TRAX



MINE TRAX

MINE TRAX is a bias-ply tyre designed for demanding requirements in underground mining operations. Specifically intended for mine utility vehicles, the tyre performs reliably in harsh underground conditions across a variety of operations and maintenance tasks, including material handling and cable installation. The non-directional tread pattern provides multi-directional versatility, while wide tread blocks ensure excellent traction and enhance vehicle stability. The large contact area and high ply rating deliver superior load capacity and maintain stability during lifting and aerial maneuvers, ensuring operator safety. In addition, the reinforced carcass and the cut-resistant sidewall protect against lateral damage, reducing machine downtime and extending the tyre's service life.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø24"	19.5 L - 24	TL	R4	14	154 A8	-	-	0		1330			44.5	STD
	19.5 L - 24	TL	R4	14	154 A8	DW 16 L	-	-		1330			44.5	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			
R4	154 kg		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026



TECHNOLOGIES		PERFORMANCES	
	 R4		
	 154 kg		
A8			

Permissible tolerances: O.D. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.