

# RIB IMPLEMENT (B)

|                           |                             |
|---------------------------|-----------------------------|
| <b>TIRE SIZE</b>          | <b>49 - 20</b>              |
| <b>UM</b>                 | US STANDARD                 |
| <b>CONSTRUCTION</b>       | ❖ BIAS                      |
| <b>MACHINERY</b>          | ARBETSFORDON / ARBETSFORDON |
| <b>VERSION</b>            | STANDARD                    |
| <b>TIRE TYPE</b>          | TT                          |
| <b>LI/SS DRIVE WHEEL</b>  | 146 A8/143 B                |
| <b>LI/SS FREE ROLLING</b> | 158 A8/154 B                |



## DIMENSIONER US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94046591 | <b>RIM ALT</b> | 14.0            |
| <b>SW (IN)</b>  | 16.7     | <b>ECE</b>     | E11-106R-004653 |
| <b>OD (IN)</b>  | 47.2     | <b>PR</b>      | 20              |
| <b>RIM REC</b>  | 13.0     |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>58</b> |
|------------------|-----------|
| <b>25 FR</b>     | 9370      |
| <b>30 FR</b>     | 8270      |
| <b>25 DW</b>     | 6610      |
| <b>30 DW</b>     | 6000      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.