


# AGRIMAX PROHARVEST

TIRE SIZE	VF 1000/55 R 32
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE RECOLTARE
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	197 D



## DIMENSIUNI IS STANDARD

SW (MM)	1006	RIM REC	36.00 VA (multi-piece)
OD (MM)	1900	ECE	E11-106R-0010574
SLR (MM)	841	SRI	900
RC (MM)	5703		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
70	4560	5265	5965	6785	7485	8300	9240	9940	10875	11690
FROM 65 TO 40	5015	5785	6555	7455	8225	9125	10155	10925	11955	12850
30	5115	5900	6690	7605	8395	9310	10360	11145	12195	13110
20	5215	6015	6820	7755	8555	9490	10560	11365	12430	13365
10	5515	6365	7210	8200	9050	10040	11170	12015	13150	14135
*UPTO 30 CYC	5690	6565	7440	8460	9335	10360	11525	12400	13565	14585
*UPTO 15 CYC	6795	7840	8885	10105	11150	12365	13760	14805	16200	17415
*UPTO 10 CYC	7445	8590	9735	11070	12215	13555	15080	16225	17750	19085
10HT	5115	5900	6690	7605	8395	9310	10360	11145	12195	13110

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.