

# FLOTATION 648

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>400/60 - 22.5</b>   |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       | BIAS   |
| <b>MACHINERY</b>          | PRESSA PER BALLE DI FIENO /<br>MIETITREBBIA / SPARGITORE /<br>MIETITREBBIA / ATTREZZI AGRICOLI |
| <b>VERSIONE</b>           | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 155 A8/151 B   |
| <b>LI/SS FREE ROLLING</b> | 167 A8/163 B   |



## DIMENSIONI US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CODICE USA</b> | 94048618 | <b>RC (IN)</b> | 127.3           |
| <b>SW (IN)</b>    | 15.7     | <b>RIM REC</b> | AG 11.75        |
| <b>OD (IN)</b>    | 42.1     | <b>ECE</b>     | E11-106R-004389 |
| <b>SLR (IN)</b>   | 18.7     | <b>PR</b>      | 22              |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI    | 77    | 81    | 86    |
|--------------|-------|-------|-------|
| <b>5 FR</b>  | 15810 | 16310 | 16820 |
| <b>10 FR</b> | 14220 | 14680 | 15130 |
| <b>20 FR</b> | 12640 | 13050 | 13460 |
| <b>25 FR</b> | 11290 | 11650 | 12010 |
| <b>30 FR</b> | 10160 | 10480 | 10750 |
| <b>5 DW</b>  | 11230 | 11610 | 11960 |
| <b>10 DW</b> | 10110 | 10450 | 10770 |
| <b>20 DW</b> | 8980  | 9280  | 9570  |
| <b>25 DW</b> | 8020  | 8290  | 8540  |
| <b>30 DW</b> | 7220  | 7460  | 7610  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.