


FORESTMAX

TIRE SIZE	600/60 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR / FORESTRY
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	152 A8 ; 149 B



DIMENSIONS US STANDARD

USA CODE	94512850	RC (IN)	169.9
SW (IN)	22.4	RIM REC	DW18L
OD (IN)	56.3	RIM ALT	DW20B
SLR (IN)	25.8	ECE	E11-106R-0010523

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35
30	4870	5450	5590	6160	6660	6880	7160
25	5320	5950	6110	6730	7270	7520	7830
20	5700	6370	6540	7210	7790	8050	8380
15	5920	6610	6790	7480	8090	8360	8700
12	6560	7330	7520	8290	8960	9260	9630
10	7140	7980	8190	9030	9750	10070	10490
5	7990	8930	9160	10100	10910	11280	11740
5 FORESTRY SERVICE	-	-	-	-	-	-	9630
0 FORESTRY SERVICE	-	-	-	-	-	-	18000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.