

# MULTIMAX MP 513

<b>TIRE SIZE</b>	<b>425/75 R 20 MPT</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VEICOLO UNIVERSALE / AUTOCARRO PER FERTILIZZANTI / VEICOLO UNIVERSALE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	148 G



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94034703	<b>RIM REC</b>	13
<b>SW (IN)</b>	16.6	<b>RIM ALT</b>	13 SDC; 11 SDC; 12 SDC; 11; 12
<b>OD (IN)</b>	45.1	<b>ECE</b>	E11-54R-0016141
<b>RC (IN)</b>	136.4		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	36	44	51	58
55	3390	3990	4740	5490	6220	6940
40	3690	4330	5150	5960	6750	7540
25	3910	4600	5460	6320	7150	7990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.