


# EARTHMAX SR 41

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
|                     | <b>29.5 R 25</b>                                                                         |
| <b>UM</b>           | US STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | YOL VE YOL DIŐI KAMYON / DOZER /<br>YÜKLEYİCİ / YÜKLEYİCİ                                |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND                                                                   |
| <b>TIRE TYPE</b>    | TL                                                                                       |



## UNDEFINED US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94051052 | <b>RIM REC</b>     | 25.00/3.5 |
| <b>OD (IN)</b>  | 73.3     | <b>TRA CODE</b>    | SH4       |
| <b>SLR (IN)</b> | 32.7     | <b>STAR RATING</b> | ★★★★      |
| <b>RC (IN)</b>  | 216.9    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.